

Carpet Heat Mat 140

>> Floor heating for under fitted carpet

FHK Carpet Heat Mat can be installed under fitted carpet, sandwiched between the carpet and underlay. Other applications include heating under rugs.



Benefits

- >> Fast & easy to install
- >> Only 1 cold lead
- >> 100% Earth protection
- >> Maintenance free
- >> 5 Year product warranty

Technical Data

Application	Heating under fitted carpet and rugs
Construction	Twin conductor heating cable with primary fluoropolymer insulation, sandwiched between two layers of reinforced aluminium foil.
Output	140W/m ² @ 230 Volt
Cable diameter	6mm
Cold lead	One 3m cold lead
IP Class	IPX7
Cable standard	IEC 60335
Warranty	5 year product warranty

Available Sizes

Stock Code	Mat Size WxL	Area	Watt	Amp	Resistance
LP140-14S	0.5 x 2m	1m ²	140W	0.6A	383.3Ω
LP210-14S	0.5 x 3m	1.5m ²	210W	0.9A	255.6Ω
LP280-14S	0.5 x 4m	2m ²	280W	1.2A	191.7Ω
LP350-14S	0.5 x 5m	2.5m ²	350W	1.5A	153.3Ω
LP420-14S	0.5 x 6m	3m ²	420W	1.8A	127.8Ω
LP490-14S	0.5 x 7m	3.5m ²	490W	2.1A	109.5Ω
LP560-14S	0.5 x 8m	4m ²	560W	2.4A	95.8Ω
LP630-14S	0.5 x 9m	4.5m ²	630W	2.7A	85.2Ω
LP700-14S	0.5 x 10m	5m ²	700W	3A	76.7Ω
LP840-14S	0.5 x 12m	6m ²	840W	3.7A	62.2Ω
LP980-14S	0.5 x 14m	7m ²	980W	4.3A	53.5Ω
LP1120-14S	0.5 x 16m	8m ²	1120W	4.9A	46.9Ω
LP1260-14S	0.5 x 18m	9m ²	1260W	5.5A	41.8Ω
LP1400-14S	0.5 x 20m	10m ²	1400W	6.1A	37.7Ω
LP1540-14S	0.5 x 22m	11m ²	1540W	6.7A	34.3Ω
LP1680-14S	0.5 x 24m	12m ²	1680W	7.3A	31.5Ω
LP2100-14S	0.5 x 30m	15m ²	2100W	9.1A	25.3Ω